



Element Materials Technology
222 Cavalcade Street
Houston, TX
77009-3213 USA

P 713 692 9151
F 713 696 6307
T 888 786 7555
info.houston@element.com
element.com

Contact: Arun Srivasatva
BSL Scaffolding USA LLC
3975 Atascocita Way
HUMBLE, TX 77396

P: 281 979 0953 / F: 281/458-3744

TEST CERTIFICATE — EAR-CONTROLLED DATA

Date: 12/15/2011
P.O. No.: Ukraine
W/O No.: BSL001-11-30-92055-1

Sample Information: 3 Tier Ring-Lock System Tower
BSL-RL-V3M 3 Meter Verticals
5' x 7' Base Dimensions

THREE TIER SYSTEM COMPRESSION TEST
TEST Method: ANSI/SSFI SC100-5/05

Set #	Max Load (lbs)	Load (lbs) per Leg	Load (lbs) per Leg at 4:1 Safety Factor
1	67,380	16,850	4,210



View of Three Tier Tower, before loading



Deflection Point at 67,380 lbs.

This document contains technical data whose export and re-export/ retransfer is subject to control by the U.S. Department of Commerce under the Export Administration Act and the Export Administration Regulations. The Department of Commerce's prior written approval may be required for the export or re-export/retransfer of such technical data to any foreign person, foreign entity or foreign organization whether in the United States or abroad.

Respectfully Submitted

Terry Wilt
Department Manager, Metals & Product Testing

Our letters and reports are for the exclusive use of the client to whom they are addressed and shall not be reproduced except in full without the approval of the testing laboratory. The use of our name must receive our written approval. Our letters and reports apply only to the sample tested and/or inspected, and are not indicative of the quantities of apparently identical or similar products. Unless otherwise noted all test methods and specifications are to the most current revision. Material submitted to our metals department will be discarded after a period of 30 days unless otherwise directed.