

**BSL SCAFFOLDING USA LLC**  
3975 Atascocita Way  
Humble, TX 77396  
P: 281-979-0953 / F: 281/458-3744

W/O. No.: BSL001-04-08-54760-2  
P.O. No.: 2  
Report Date: 4/8/2009

**Identification:** 5' Ledger

| Test Type    | Maximum Applied Load (lbs) | Load (lbs) at 3:1 Safety Factor |
|--------------|----------------------------|---------------------------------|
| Point Load   | 2,165                      | 720                             |
| Uniform Load | 2,935                      | 975                             |



Point Load



Point Load at 2,165 lbs.



Uniform Load




Uniform Load at 2,935 lbs.

Our letters and reports are for the exclusive use of the client to whom they are addressed and shall not be reproduced except in full without the approval of the testing laboratory. The use of our name must receive our written approval. Our letters and reports apply only to the sample tested and/or inspected, and are not indicative of the quantities of apparently identical or similar products. Material submitted to our metals department will be discarded after a period of 30 days unless otherwise directed.

Stork SWL, is an operating unit of Stork Materials Technology B.V., Amsterdam, The Netherlands, which is a member of the Stork group

**Respectfully Submitted**

  
Terry Wilt  
Manager, Product Evaluation